

# KD90HNE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709243609
Hood width	90 cm



## Aesthetics

Aesthetic	Classica	Serigraphy colour	Black
Colour	Black	Logo	Applied
Finishing	Glossy		



## Controls

Control setting	Control knobs	Control knobs	Classic
No. of controls	2	Controls colour	Steel effect

## Programme / Functions

No. of speeds	3
Intensive speed	

## Technical Features

			
No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Stainless steel
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (°K)	4000 °K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	815 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W		

Non return valve

Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2- 13 [dB(A)]
Speed 1	288	48
Speed 2	421	63
Speed 3	630	67
Intensive speed	781	72

## Performance / Energy Label

A+

**Annual Efficiency Consumption (AEChood)** 40 kWh/a  
**Energy efficiency class (EEC)** A+  
**Fluid Dynamic Efficiency (FDE)** 36,2  
**Fluid Dynamic Efficiency class (FDEC)** A  
**Lighting Efficiency (LE)** 78,2 lux/W  
**Lighting Efficiency Class (LEC)** A  
**Grease Filtering Efficiency (GFE)** 78,5 %  
**Grease Filtering Efficiency Class (GFEC)** C  
**Air flow at minumum speed (Qmin)** 288 m³/h  
**Air flow at maximum speed (Qmax)** 630 m³/h  
**Air flow at boost speed (Qboost)** 781 m³/h

**Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)** 48 dB(A)  
**Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** 67 dB(A)  
**Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)** 72 dB(A)  
**Time increase factor (F)** 1,00  
**Measured air flow rate at best efficiency point (Qbep)** 413 m³/h  
**Measured air pressure at best efficiency point (Pbep)** 476 Pa  
**Measured electric power input at best efficiency point (Wbep)** 151 W  
**Nominal Power consumption of the light system (WL)** 2 W  
**Average illumination of the light on the cooking surface (Emiddle)** 172 lux  
**Sound power level at highest setting (Lwa)** 67 dB(A)

## Electrical Connection

**Electrical connection rating** 277 W  
**Voltage** 220-240 V

**Frequency (Hz)** 50-60 Hz  
**Power supply cable length** 1000 mm

## Also available

Alternative colours  
available

Stainless steel, Anthracite


Available colours

KD90HXE - KD90HAE

## Optional accessories

Charcoal filter

FLT6



---

## Not included accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary (TT)

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**A+:** Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**Intensive/turbo setting:** when extra fast extraction is required.