


## KDH12WLD

Hood, Fully Integrated, Universal, Black, 12 cm, A+



### INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



### PERIMETER EXTRACTION

This is an extremely efficient extraction process where vapors are drawn in through a restricted area of the hood quickly and then decrease once inside which reduces noise as it limits the vibrations of the filters.



### TYPE

Product family: Hood • Hood Type: Fully Integrated • Hood width: 12 cm • Extraction: Expulsion • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709277826

### AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universal • Design: Fully integrated • Material: Glass • Glass Type: Black

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Touch control • Led colour: Ice • Display: Digital

### TECHNICAL FEATURES

Free outlet maximum capacity: 570 m<sup>3</sup>/h • Motor power: 145 W • No. of filters: 1 • Anti-grease filters: Stainless steel • Filter replacement indicator: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): NA • Annual Efficiency Consumption (AEC<sub>hood</sub>): 37 kWh/year • Fluid Dynamic Efficiency (FDE): 32 • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q<sub>min</sub>): 370 m<sup>3</sup>/h • Maximum extraction rate: 470 m<sup>3</sup>/h • Intensive extraction rate: 550 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 62 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 69 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 72 dB(A) • Power Consumption in Off mode (P<sub>o</sub>): 0.49 W • Time increase factor (F): 0.8 • Energy Efficiency Index per first cavity: 43.4 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 295 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Q<sub>bep</sub>): 490 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 125 W • Sound power level at highest setting (L<sub>wa</sub>): 72 dB(A)

## ELECTRICAL CONNECTION

Nominal power: 145 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## SPEED 1

Extraction rate IEC 61591: 370 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 60 W

## SPEED 2

Extraction rate IEC 61591: 420 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 80 W

## SPEED 3

Extraction rate IEC 61591: 470 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 69 dB(A) • Power: 110 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 550 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 145 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 215x115x510 • Width: 115 mm • Depth (mm): 510 mm • Product Height (mm): 215 mm

## ACCESSORIES INCLUDED

Sliding door: Yes

## OPTIONAL

CFKDH12HP: Charcoal filter, HoodsCFKDH12STD: Charcoal filter, HoodsFLMSTPKDH12: Flame guard, HoodsFLTKDH: Anti-odour filter, HoodsGRIDKDH12: Filter grid, Hoods

