



KEIV90E

Hood, Decorative island hood, Universal, Stainless steel, 90 cm, A



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Ducted out or re-circulation possible • Electronic control: Yes • EAN code: 8017709208745

AESTHETICS

Colour: Stainless steel • Finishing: Glass • Aesthetics: Universal • Design: T flat • Material: Glass • Type of steel: Brushed • Glass Type: Clear

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Electronic buttons

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light power: 1 W • Free outlet maximum capacity: 720 m³/h • Motor power: 270 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 58 kWh/year • Fluid Dynamic Efficiency (FDE): 29.7 • Lighting Efficiency (LE): 100 lux/W • Grease Filtering Efficiency (GFE): 80 % • Air flow at minimum speed (Q_{min}): 300 m³/h • Maximum extraction rate: 560 m³/h • Intensive extraction rate: 700 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 56 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 66 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 70 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index per first cavity: 53 • Measured air flow rate at best efficiency point (Q_{bep}): 390 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 460 Pa • Measured electric power input at best efficiency point (W_{bep}): 168 W • Normal Power of the light system (W_I): 4 W • Average illumination of the light on the cooking surface (E_{middle}): 440 lux • Sound power level at highest setting (L_{wa}): 66 dB(A)

ELECTRICAL CONNECTION

Nominal power: 274 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 300 m³/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 175 W

SPEED 2

Extraction rate IEC 61591: 400 m³/h • Noise level IEC 60704-2-13: 60 dB(A) • Power: 220 W

SPEED 3

Extraction rate IEC 61591: 560 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 255 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 700 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 270 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 922x900x700 • Width: 900 mm • Depth (mm): 700 mm • Product Height (mm): 922 mm • Net weight (kg): 28.200 kg • Gross weight (kg): 37.900 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC161: Charcoal filter, Hoods

