



KFAB75CR

Hood, Decorative wall hood, 50's Style , Cream, 75 cm, A+



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 75 cm • Extraction: Re-circulation only • Electronic control: Yes • EAN code: 8017709224875

AESTHETICS

Colour: Cream • Finishing: Gloss • Aesthetics: 50's Style • Design: Angled • Material: Painted material • Type of steel: Brushed

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led colour: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 280 W • No. of filters: 3 • Anti-grease filters: Stainless steel • Charcoal filters included: Yes • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 36 kWh/year • Fluid Dynamic Efficiency (FDE): 36.6 • Lighting Efficiency (LE): 68.2 lux/W • Grease Filtering Efficiency (GFE): 61.1 % • Air flow at minimum speed (Q_{min}): 333 m³/h • Maximum extraction rate: 649 m³/h • Intensive extraction rate: 797 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 67 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 72 dB(A) • Power consumption in stand-by mode (P_s): 0.7 W • Time increase factor (F): 0.49 • Energy Efficiency Index per first cavity: 39.7 • Measured air flow rate at best efficiency point (Q_{bep}): 421 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 422 Pa • Measured electric power input at best efficiency point (W_{bep}): 135 W • Normal Power of the light system (W_I): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 150 lux • Sound power level at highest setting (L_{wa}): 67 dB(A)

ELECTRICAL CONNECTION

Nominal power: 282 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 333 m³/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 198 W

SPEED 2

Extraction rate IEC 61591: 477 m³/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 246 W

SPEED 3

Extraction rate IEC 61591: 649 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 286 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 797 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 294 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 644x750x616 • Width: 750 mm • Depth (mm): 616 mm • Product Height (mm): 644 mm • Net weight (kg): 26.000 kg • Gross weight (kg): 32.400 kg

ACCESSORIES INCLUDED

Sliding door: Yes Remote control: Yes

OPTIONAL

FLTSI: Charcoal filter, Hoods

