



KI120XE

Hood, Decorative island hood, Universal, Stainless steel, 120 cm, B



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 120 cm • Extraction: Ducted out or re-circulation possible • Electronic control: Yes • EAN code: 8017709204051

AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: T flat • Material: Stainless steel • Type of steel: Brushed

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led colour: White

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 4 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Minimum distance from ELECTRIC hob: 650 mm • Vent outlet: 150 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 64 kWh/year • Fluid Dynamic Efficiency (FDE): 28.7 • Lighting Efficiency (LE): 70.9 lux/W • Grease Filtering Efficiency (GFE): 79.8 % • Air flow at minimum speed (Q_{min}): 316 m³/h • Maximum extraction rate: 529 m³/h • Intensive extraction rate: 783 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 48 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 62 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 70 dB(A) • Power Consumption in Off mode (P_o): 0.71 W • Time increase factor (F): 1.00 • Energy Efficiency Index per first cavity: 58.7 • Measured air flow rate at best efficiency point (Q_{bep}): 394 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 449 Pa • Measured electric power input at best efficiency point (W_{bep}): 171 W • Normal Power of the light system (W_l): 4 W • Average illumination of the light on the cooking surface (E_{middle}): 312 lux • Sound power level at highest setting (L_{wa}): 62 dB(A)

ELECTRICAL CONNECTION

Nominal power: 279 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 316 m³/h • Noise level IEC 60704-2-13: 48 dB(A) • Power: 203 W

SPEED 2

Extraction rate IEC 61591: 385 m³/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 240 W

SPEED 3

Extraction rate IEC 61591: 529 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 248 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 783 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 276 W

