



## KlgoXE

Hood, Decorative island hood, Universal, Stainless steel, 90 cm, B



### INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



### TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Expulsion • Electronic control: Yes •

EAN code: 8017709204044

### AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: T flat • Material: Stainless steel • Type of steel:

Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons • Led colour: White

### TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class ( EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 66 kWh/year • Fluid Dynamic Efficiency (FDE): 27.4 • Lighting Efficiency (LE): 88.6 lux/W • Grease Filtering Efficiency (GFE): 83.1 % • Air flow at minimum speed (Q<sub>min</sub>): 311 m<sup>3</sup>/h • Maximum extraction rate: 533 m<sup>3</sup>/h • Intensive extraction rate: 740 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 63 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 71 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.49 W • Energy Efficiency Index per first cavity: 58.8 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 390 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Q<sub>bep</sub>): 451 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 171 W • Normal Power of the light system (W<sub>l</sub>): 4 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 390 lux • Sound power level at highest setting (L<sub>wa</sub>): 63 dB(A)

## ELECTRICAL CONNECTION

Nominal power: 279 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## SPEED 1

Extraction rate IEC 61591: 311 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 203 W

## SPEED 2

Extraction rate IEC 61591: 385 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 240 W

## SPEED 3

Extraction rate IEC 61591: 533 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 248 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 740 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 276 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 880x900x600 • Width: 900 mm • Depth (mm): 600 mm • Product Height (mm): 880 mm

## ACCESSORIES INCLUDED

Tube reduction: Yes

## OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

