


KICV90BL

Hood, Decorative wall hood, Universal, Black, 90 cm, A+



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



PERIMETER EXTRACTION

This is an extremely efficient extraction process where vapors are drawn in through a restricted area of the hood quickly and then decrease once inside which reduces noise as it limits the vibrations of the filters.



CLEAN AIR

The 24h air exchange function makes the hood work for 10 minutes every hour at very low speed and therefore without noise for a total of 24 hours in order to purify the air of the house, with low energy impact.



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Ducted out or re-circulation possible
 • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709262150

AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universal • Design: Angled • Material: Glass • Glass Type: Black

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Auto-Vent: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Touch control • Led colour: Red

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1 W • Free outlet maximum capacity: 750 m³/h • Motor power: 270 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 450 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 450 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): F • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 41 KWh/year • Fluid Dynamic Efficiency (FDE): 34.8 • Lighting Efficiency (LE): 68 lux/W • Grease Filtering Efficiency (GFE): 45.1 % • Air flow at minimum speed (Q_{min}): 310 m³/h • Maximum extraction rate: 580 m³/h • Intensive extraction rate: 720 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 62 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 65 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 0.7 • Energy Efficiency Index per first cavity: 40.5 • Measured air flow rate at best efficiency point (Q_{bep}): 470 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 470 Pa • Measured electric power input at best efficiency point (W_{bep}): 154 W • Normal Power of the light system (W_l): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 150 lux • Sound power level at highest setting (L_{wa}): 62 dB(A)

ELECTRICAL CONNECTION

Nominal power: 272 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 310 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 175 W

SPEED 2

Extraction rate IEC 61591: 420 m³/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 220 W

SPEED 3

Extraction rate IEC 61591: 580 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 255 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 720 m³/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 270 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 1032x898x378 • Width: 898 mm • Depth (mm): 378 mm • Product Height (mm): 1032 mm •
Net weight (kg): 13.900 kg • Gross weight (kg): 17.300 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC152: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

