


KSEG78PXE

Hood, Integrated hood, Universal, Stainless steel, 77 cm, A



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



PERIMETER EXTRACTION

This is an extremely efficient extraction process where vapors are drawn in through a restricted area of the hood quickly and then decrease once inside which reduces noise as it limits the vibrations of the filters.



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 77 cm • Extraction: Ducted out or re-circulation possible • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709224905

AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led colour: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 673 m³/h • Motor power: 275 W • No. of filters: 2 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 46 kWh/year • Fluid Dynamic Efficiency (FDE): 31.7 • Lighting Efficiency (LE): 111.8 lux/W • Grease Filtering Efficiency (GFE): 56.9 % • Air flow at minimum speed (Q_{min}): 261 m³/h • Maximum extraction rate: 606 m³/h • Intensive extraction rate: 683 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 46 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 65 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 68 dB(A) • Power consumption in stand-by mode (P_s): 0.49 W • Time increase factor (F): 0.9 • Measured air flow rate at best efficiency point (Q_{bep}): 329 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 466 Pa • Measured electric power input at best efficiency point (W_{bep}): 134 W • Normal Power of the light system (W_l): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 246 lux • Sound power level at highest setting (L_{wa}): 65 dB(A)

ELECTRICAL CONNECTION

Nominal power: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 261 m³/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 199 W

SPEED 2

Extraction rate IEC 61591: 436 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 219 W

SPEED 3

Extraction rate IEC 61591: 606 m³/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 233 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 683 m³/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 228 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 335x770x300 • Width: 770 mm • Depth (mm): 300 mm • Product Height (mm): 335 mm • Net weight (kg): 11.150 kg • Gross weight (kg): 13.000 kg

OPTIONAL

FLT4: Charcoal filter kit, Hoods

