

## KSET900XE

Hood, Integrated (semi), Universal, Stainless steel, 90 cm, B



### TYPE

Product family: Hood • Hood Type: Integrated (semi) • Hood width: 90 cm • Extraction: Ducted out or re-circulation possible •

EAN code: 8017709205379

### AESTHETICS

Colour: Stainless steel • Finishing: Brushed • Aesthetics: Universal • Design: Telescopic • Material: Stainless steel • Type of steel: Brushed

### PROGRAMS / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 3 W • Light color temperature scale (°K): 3500 °K • Free outlet maximum capacity: 600 m<sup>3</sup>/h • Motor power: 175 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): C • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 75 kWh/year • Fluid Dynamic Efficiency (FDE): 21 • Lighting Efficiency (LE): 76.1 lux/W • Grease Filtering Efficiency (GFE): 76 % • Air flow at minimum speed (Q<sub>min</sub>): 240 m<sup>3</sup>/h • Maximum extraction rate: 581 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 44 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 65 dB(A) • Time increase factor (F): 1.2 • Energy Efficiency Index per first cavity: 69.4 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 352 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Q<sub>bep</sub>): 354 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 165 W • Normal Power of the light system (W<sub>I</sub>): 4 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 304 lux • Sound power level at highest setting (L<sub>wa</sub>): 65 dB(A)

## ELECTRICAL CONNECTION

Nominal power: 215 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 240 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 44 dB(A) • Power: 108 W

### SPEED 2

Extraction rate IEC 61591: 368 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 137 W

### SPEED 3

Extraction rate IEC 61591: 581 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 199 W

### SPEED 4

## INTENSIVE SPEED

## LOGISTIC INFORMATION

Dimensions of the product (mm): 324x898x300 • Width: 898 mm • Depth (mm): 300 mm • Product Height (mm): 324 mm • Net weight (kg): 12.000 kg • Gross weight (kg): 14.100 kg

## OPTIONAL

KITFC500: Charcoal filter, Hoods



