


KSG70E

Hood, Integrated hood, Universal, Silver, 73 cm, C



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 73 cm • Extraction: Ducted out or re-circulation possible •

EAN code: 8017709275136

AESTHETICS

Colour: Silver • Aesthetics: Universal • Design: Fully integrated • Material: Painted material

PROGRAMS / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 3 W • Light color temperature scale (°K): 2700 °K • Free outlet maximum capacity: 232 m³/h • Motor power: 75 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 120 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): C • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC_{hood}): 50 kWh/year • Fluid Dynamic Efficiency (FDE): 8.8 • Lighting Efficiency (LE): 13 lux/W • Grease Filtering Efficiency (GFE): 56 % • Air flow at minimum speed (Q_{min}): 125 m³/h • Maximum extraction rate: 224 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 45 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 54 dB(A) • Time increase factor (F): 1.7 • Energy Efficiency Index per first cavity: 84.7 • Measured air flow rate at best efficiency point (Q_{bep}): 160 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 145 Pa • Measured electric power input at best efficiency point (W_{bep}): 74 W • Normal Power of the light system (W_l): 6 W • Average illumination of the light on the cooking surface (E_{middle}): 78 lux • Sound power level at highest setting (L_{wa}): 54 dB(A)

ELECTRICAL CONNECTION

Nominal power: 81 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 125 m³/h • Noise level IEC 60704-2-13: 45 dB(A) • Power: 45 W

SPEED 2

Extraction rate IEC 61591: 155 m³/h • Noise level IEC 60704-2-13: 47 dB(A) • Power: 59 W

SPEED 3

Extraction rate IEC 61591: 224 m³/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 75 W

SPEED 4

INTENSIVE SPEED

LOGISTIC INFORMATION

Dimensions of the product (mm): 208x734x257 • Width: 734 mm • Depth (mm): 257 mm • Product Height (mm): 208 mm • Net weight (kg): 4.300 kg • Gross weight (kg): 7.120 kg

OPTIONAL

KITFC62: Charcoal filter, Hoods

