



KT100BLE

Hood, Decorative wall hood, Victoria, Black, 100 cm, A



INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or a preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 100 cm • Extraction: Expulsion • EAN code: 8017709244033

AESTHETICS

Colour: Black • Finishing: Gloss • Aesthetics: Victoria • Design: Chimney • Material: Painted material • Type of steel: Brushed

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Control knobs • Control knobs: Victoria • No. of controls: 2 • Controls colour: Steel effect

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 2 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 48 kWh/year • Fluid Dynamic Efficiency (FDE): 34.2 • Lighting Efficiency (LE): 76.8 lux/W • Grease Filtering Efficiency (GFE): 81 % • Air flow at minimum speed (Q_{min}): 334 m³/h • Maximum extraction rate: 606 m³/h • Intensive extraction rate: 787 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 51 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 64 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 73 dB(A) • Time increase factor (F): 1.00 • Energy Efficiency Index per first cavity: 46.2 • Measured air flow rate at best efficiency point (Q_{bep}): 412 m³/h • Measured air pressure at best efficiency point (Q_{bep}): 478 Pa • Measured electric power input at best efficiency point (W_{bep}): 160 W • Normal Power of the light system (W_l): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 169 lux • Sound power level at highest setting (L_{wa}): 64 dB(A)

ELECTRICAL CONNECTION

Nominal power: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 334 m³/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 198 W

SPEED 2

Extraction rate IEC 61591: 424 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 227 W

SPEED 3

Extraction rate IEC 61591: 606 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 248 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 787 m³/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 286 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 750x1000x480 • Width: 1000 mm • Depth (mm): 480 mm • Product Height (mm): 750 mm •

Net weight (kg): 18.400 kg

OPTIONAL

FLT6: Charcoal filter, HoodskITALLFC: Charcoal filter, Hoods

