

## HOB682D

Hob, Aesthetics: Universale, Induction with integrated hood, 80 cm, Black, Built-in type: Ultra-low profile or Fully Flushed



### TYPE

Product Family: Hob • Extraction: Extraction • EAN code: 8017709279783 • Dimensions: 80 cm • Power supply: Electric • Built-in type: Ultra-low profile or Fully Flushed • Type: Induction with integrated hood • Electronic control: Yes

### AESTHETICS

Glass edge: Straight edge • Type of control setting: Touch controls • Slider: Yes • Finishing: Glass • Aesthetics: Universale • Glass type: Ceramic • Control knob position: Front • Serigraphy colour: Grey • Colour: Black • Material: Glass • Pan stands: Cast iron

### PROGRAMS / FUNCTIONS

Total no. of cook zones: 4 • No. of induction cook zones: 4 • No. of Flexible zones: 2 • Auto-Vent: Yes • No. of cooking zones with booster: 4 • Time-setting options: Spegnimento automatico • Power levels: 9 • Main on/off switch: Yes

### OPTIONS

Flexible Zone Type: MultiZone • Rapid level selection: Yes • End cooking timer: 4 • Residual time indicator: Yes • Quick start: Yes • Control Lock / Child Safety: Yes • Keep warm automatic function: Yes • Multizone Option: Yes • Pause option: Yes • Minute minder: 1 • Melting/Low temperature cooking function: Yes • End of cooking alarm: Yes • Simmering Function: Yes

## COOKING ZONES

Booster power right Multizone: 3.70 kW • 4th zone dimensions: 23.0x21.0 cm • 3rd zone dimensions: 23.0x21.0 cm • Booster power left Multizone: 3.70 kW • 4th zone type: Induction - Multizone • 1st zone booster power: 3.70 kW • 2nd zone booster power: 3.70 kW • 2nd zone type: Induction - Multizone • 2nd zone dimensions: 23.0x21.0 cm • 3rd zone booster power: 3.70 kW • 3rd zone type: Induction - Multizone • 1st zone dimensions: 23.0x21.0 cm • 4th zone booster power: 3.70 kW • 2nd zone power: 2.10 kW • 1st zone power: 2.10 kW • 4th zone power: 2.10 kW • 3rd zone power: 2.10 kW • Right Multizone dimension: 460x210 mm • 4th zone position: Front-right • 3rd zone position: Rear-right • 1st zone type: Induction - Multizone • 2nd zone position: Rear-left • 1st zone position: Front-left • Left Multizone dimension: 460x210 mm

## TECHNICAL FEATURES

Automatic switch off when overflow: Yes • Automatic setting according to pan dimension: Yes • Protection against accidental start up: Yes • Residual heat indicator: Yes • pan detection: Yes

## PERFORMANCE / ENERGY LABEL

Energy consumption zone 3: 170 Wh/Kg • 2nd zone energy consumption: 170 Wh/Kg • Energy consumption zone 4: 170 Wh/Kg

## ELECTRICAL CONNECTION

Voltage (V): 220-240 V • Frequency (Hz): 50/60 Hz • Type of electric cable: Single and Double phase • Electrical connection rating (W): 7545 W

## CONTROLS (HOOD)

Display: Yes • Hood control setting: Touch Capacitive • Led color: Bianco

## PROGRAMS / FUNCTIONS (HOOD)

Auto-Vent: Yes • No. of speeds: 8 • Intensive speed: 2 • Hood time setting: Delay • Other functions: AUTOVENT

## TECHNICAL FEATURES (HOOD)

Free outlet maximum capacity: 750 m<sup>3</sup>/h • Motor power: 220 W • Anti-grease filters: Inox • No. of filters: 1 • Filter replacement indicator: Yes

## SPEED 1

Power: 13 W • Noise level IEC 60704-2-13: 42 dB(A) • Extraction rate IEC 61591: 145 m<sup>3</sup>/h

## SPEED 2

Power: 15 W • Noise level IEC 60704-2-13: 46 dB(A) • Extraction rate IEC 61591: 155 m<sup>3</sup>/h

## SPEED 3

Power: 20 W • Extraction rate IEC 61591: 200 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A)

## SPEED 4

Extraction rate IEC 61591: 270 m<sup>3</sup>/h • Power: 25 W • Noise level IEC 60704-2-13: 55 dB(A)

## SPEED 5

Noise level IEC 60704-2-13: 58 dB(A) • Pressure: 140 Pa • Power: 30 W • Extraction rate IEC 61591: 300 m<sup>3</sup>/h

## SPEED 6

Pressure: 180 Pa • Noise level IEC 60704-2-13: 59 dB(A) • Extraction rate IEC 61591: 340 m<sup>3</sup>/h • Power: 35 W

## SPEED 7

Noise level IEC 60704-2-13: 64 dB(A) • Extraction rate IEC 61591: 420 m<sup>3</sup>/h • Power: 45 W • Pressure: 270 Pa

## SPEED 8

Noise level IEC 60704-2-13: 66 dB(A) • Extraction rate IEC 61591: 500 m<sup>3</sup>/h • Power: 65 W • Pressure: 380 Pa

## INTENSIVE SPEED

Extraction rate (IEC 61591): 620 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 74 dB(A) • Power: 110 W

## INTENSIVE SPEED 2

Pressure: 820 Pa • Power: 220 W • Extraction rate IEC 61591: 710 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 78 dB(A)

## PERFORMANCE / ENERGY LABEL (HOOD)

Air flow at maximum speed (Q<sub>max</sub>): 500 m<sup>3</sup>/h • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 414 m<sup>3</sup>/h • Fluid Dynamic Efficiency (FDE): 37.60 • Air flow at minimum speed (Q<sub>min</sub>): 145 m<sup>3</sup>/h • Annual Efficiency Consumption (AEC<sub>hood</sub>): 31.5 kWh/a • Grease Filtering Efficiency (GFE): 85.1 % • Grease Filtering Efficiency Class (GFEC): B • Power Consumption in Off mode (P<sub>o</sub>): 0.49 W • Measured air pressure at best efficiency point (P<sub>bep</sub>): 471 Pa • Fluid Dynamic Efficiency class (FDEC): A • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 66 dB(A) • Energy efficiency class (EEC): A++ • Time increase factor (F): 0.6 • Air flow at boost speed (Q<sub>boost</sub>): 710 m<sup>3</sup>/h • Lighting Efficiency Class (LEC): NA • Lighting Efficiency (LE): 0.0 lux /W • Energy Efficiency Index: 33.3 • Measured electric power input at best efficiency point (W<sub>bep</sub>): 144 W • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 78 dB(A) • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 42 dB(A) • Sound power level at highest setting (L<sub>wa</sub>): 66 dB(A)

## LOGISTIC INFORMATION

Dimensions of the product (mm): 210x830x520 • Width (mm): 830 mm • Depth (mm): 520 mm • Product Height (mm): 210 mm

## OPTIONAL

KITF6HOBD: Recirculating kit, HobsFLTHOBD: Ceramic Filter, HobsKITEHOBD: Exhaust kit, HobsTPK: Teppanyaki grill, HobsGRIDDLE: Grill, Cookers, Hobs



