


KCH62X

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, B



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709310288

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Material: Stainless steel • Type of steel:

Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Electronic buttons • Led color: White • Display: 1 a LED

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 2 W • Light color temperature scale (°K): 3500 °K • Free outlet maximum capacity: 650 m³/h • Motor power: 250 W • No. of filters: 3 • Anti-grease filters: Aluminium • Charcoal filters included: Yes • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Minimum distance from ELECTRIC hob: 500 mm • Vent outlet: 150 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): C • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 75 kWh/a • Fluid Dynamic Efficiency (FDE): 21.1 • Lighting Efficiency (LE): 76.1 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q_{min}): 245 m³/h • Air flow at maximum speed (Q_{max}): 500 m³/h • Air flow at boost speed (Q_{boost}): 600 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 46 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 64 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 68 dB(A) • Power consumption in stand-by mode (P_s): 0.49 W • Time increase factor (F): 1.2 • Energy Efficiency Index: 69.6 • Measured air flow rate at best efficiency point (Q_{bep}): 370 m³/h • Measured air pressure at best efficiency point (P_{bep}): 335 Pa • Measured electric power input at best efficiency point (W_{bep}): 163 W • Nominal Power consumption of the light system (WL): 5 W • Average illumination of the light on the cooking surface (E_{middle}): 381 lux • Sound power level at highest setting (L_{wa}): 64 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 255 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 245 m³/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 86 W

SPEED 2

Extraction rate IEC 61591: 375 m³/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 95 W

SPEED 3

Extraction rate IEC 61591: 500 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 117 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 600 m³/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 138 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 710x598x400 • Width: 598 mm • Depth (mm): 400 mm • Product Height (mm): 710 mm • Net weight (kg): 8.000 kg • Gross weight (kg): 10.200 kg

OPTIONAL

KITFC500: Charcoal filter, Hoods

