

KCV9SGE

Hood, Decorative wall hood, Linea, Stainless steel, 90 cm, B



TYPE

Hood width: 90 cm • Product family: Hood • Extraction: Extraction • EAN code: 8017709206994 • Hood Type: Decorative wall hood • Perimeter extraction: Yes • Electronic control: Yes

AESTHETICS

Aesthetics: Linea • Design: Angled • Type of steel: Brushed • Glass Type: Stopsol • Colour: Stainless steel • Finishing: Glass • Material: Glass

CONTROLS

Display: Yes • Control setting: Touch control • Led color: Ice

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off

TECHNICAL FEATURES

Dimmer mode: Yes • Anti-grease filters: Stainless steel • Light Power: 1 W • Minimum distance from GAS hob: 467 mm • Non return valve: Yes • No. of filters: 1 • No. of lights: 2 • Free outlet maximum capacity: 815 m³/h • Motor power: 275 W • Light type: LED • Vent outlet: 150 mm • Filter replacement indicator: Yes • Minimum distance from ELECTRIC hob: 467 mm

PERFORMANCE / ENERGY LABEL

Air flow at minimum speed (Qmin): 218 m³/h • Average illumination of the light on the cooking surface (Emiddle): 218 lux • Power Consumption in Off mode (Po): 0.49 W • Fluid Dynamic Efficiency class (FDEC): A • Energy efficiency class (EEC): B • Time increase factor (F): 1.00 • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 70 dB(A) • Sound power level at highest setting (Lwa): 65 dB(A) • Air flow at maximum speed (Qmax): 600 m³/h • Measured air flow rate at best efficiency point (Qbep): 384 m³/h • Fluid Dynamic Efficiency (FDE): 28.6 • Annual Efficiency Consumption (AEChood): 58.9 kWh/a • Grease Filtering Efficiency (GFE): 42.2 % • Grease Filtering Efficiency Class (GFEC): G • Measured air pressure at best efficiency point (Pbep): 428 Pa • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 65 dB(A) • Nominal Power consumption of the light system (WL): 2 W • Air flow at boost speed (Qboost): 734 m³/h • Lighting Efficiency Class (LEC): A • Lighting Efficiency (LE): 99.1 lux/W • Energy Efficiency Index: 57.4 • Measured electric power input at best efficiency point (Wbep): 160 W • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 42 dB(A)

ELECTRICAL CONNECTION

Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Electrical connection rating: 278 W

SPEED 1

Power: 82 W • Noise level IEC 60704-2-13: 42 dB(A) • Extraction rate IEC 61591: 218 m³/h

SPEED 2

Power: 142 W • Noise level IEC 60704-2-13: 63 dB(A) • Extraction rate IEC 61591: 322 m³/h

SPEED 3

Power: 268 W • Extraction rate IEC 61591: 600 m³/h • Noise level IEC 60704-2-13: 65 dB(A)

INTENSIVE SPEED

Extraction rate (IEC 61591): 734 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 268 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 908x900x410 • Width: 900 mm • Depth (mm): 410 mm • Product Height (mm): 908 mm

OPTIONAL

KITFTS: Kit, HoodsKITFCg06: Charcoal filter, Hoods

