


## KD150HXE

Hood, Decorative wall hood, Classica, Stainless steel, 150 cm, A+



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 150 cm • Extraction: Extraction • EAN code: 8017709276898

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Classica • Design: Chimney • Material: Stainless steel • Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Control knobs • Control knobs: Classic • No. of controls: 2 • Controls colour: Steel effect

### TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 830 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 5 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 41 kWh/a • Fluid Dynamic Efficiency (FDE): 36 • Lighting Efficiency (LE): 59.8 lux/W • Grease Filtering Efficiency (GFE): 71.3 % • Air flow at minimum speed (Qmin): 292 m<sup>3</sup>/h • Air flow at maximum speed (Qmax): 626 m<sup>3</sup>/h • Air flow at boost speed (Qboost): 787 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 68 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A) • Time increase factor (F): 0.7 • Energy Efficiency Index: 41.3 • Measured air flow rate at best efficiency point (Qbep): 382 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Pbep): 496 Pa • Measured electric power input at best efficiency point (Wbep): 146 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (Emiddle): 263 lux • Sound power level at highest setting (Lwa): 68 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 279 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 292 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 167 W

### SPEED 2

Extraction rate IEC 61591: 415 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 214 W

### SPEED 3

Extraction rate IEC 61591: 626 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 244 W

### SPEED 4

## INTENSIVE SPEED

Extraction rate (IEC 61591): 787 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 277 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 800x1500x539 • Width: 1500 mm • Depth (mm): 539 mm • Product Height (mm): 800 mm •

Net weight (kg): 26.100 kg • Gross weight (kg): 32.580 kg

## OPTIONAL

KITALLFC: Charcoal filter, HoodsFLT6: Charcoal filter, Hoods

