

KD9XE

Hood, Decorative wall hood, Universale, Stainless steel, 90 cm, D



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • EAN code: 8017709203030

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 1 • Light type: LED • Light Power: 4 W • Free outlet maximum capacity: 415 m³/h • Motor power: 110 W • No. of filters: 1 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): E • Annual Efficiency Consumption (AEChood): 59 kWh/a • Fluid Dynamic Efficiency (FDE): 9.3 • Lighting Efficiency (LE): 11 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Qmin): 210 m³/h • Air flow at maximum speed (Qmax): 400 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 64 dB(A) • Time increase factor (F): 1.7 • Measured air flow rate at best efficiency point (Qbep): 195 m³/h • Measured air pressure at best efficiency point (Pbep): 155 Pa • Measured electric power input at best efficiency point (Wbep): 90 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (Emiddle): 45 lux • Sound power level at highest setting (Lwa): 64 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 109 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 210 m³/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 70 W

SPEED 2

Extraction rate IEC 61591: 250 m³/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 85 W

SPEED 3

Extraction rate IEC 61591: 400 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 105 W

SPEED 4

INTENSIVE SPEED

LOGISTIC INFORMATION

Dimensions of the product (mm): 620x898x471 • Width: 898 mm • Depth (mm): 471 mm • Product Height (mm): 620 mm • Net weight (kg): 8.300 kg • Gross weight (kg): 10.500 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC155: Charcoal filter, Hoods



