

## KDE600EX

Hood, Decorative wall hood, Universale, Stainless steel, 60 cm, D



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709235154

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Components finishing: Stainless steel • Material: Stainless steel • Type of steel: Brushed

### PROGRAMME / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Buttons

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 3 W • Light color temperature scale (°K): 2700 °K • Free outlet maximum capacity: 588 m<sup>3</sup>/h • Motor power: 180 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 700 mm • Minimum distance from ELECTRIC hob: 500 mm • Vent outlet: 150 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class ( EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): C • Annual Efficiency Consumption (AEC<sub>hood</sub>): 103 kWh/a • Fluid Dynamic Efficiency (FDE): 12.6 • Lighting Efficiency (LE): 16.1 lux/W • Grease Filtering Efficiency (GFE): 76 % • Air flow at minimum speed (Q<sub>min</sub>): 208 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 559 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 44 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 67 dB(A) • Time increase factor (F): 1.5 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 320 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 255 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 180 W • Nominal Power consumption of the light system (WL): 6 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 97 lux • Sound power level at highest setting (L<sub>wa</sub>): 67 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 186 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 202 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 42 dB(A) • Power: 99 W

### SPEED 2

Extraction rate IEC 61591: 307 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 126 W

### SPEED 3

Extraction rate IEC 61591: 553 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 201 W

### SPEED 4

## INTENSIVE SPEED

## LOGISTIC INFORMATION

Dimensions of the product (mm): 529x598x450 • Width: 598 mm • Depth (mm): 450 mm • Product Height (mm): 529 mm • Net weight (kg): 6.700 kg • Gross weight (kg): 8.520 kg

## ACCESSORIES INCLUDED

Tube reduction: Yes

## OPTIONAL

KITFC450: Charcoal filter, Hoods

