

KDH12WLD

Hood, Fully Integrated hood, Universale, Black, 12 cm, A+



TYPE

Product family: Hood • Hood Type: Fully Integrated hood • Hood width: 12 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709277826

AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universale • Design: Fully integrated • Material: Glass • Glass Type: ceramic Eclipse

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Touch control • Led color: Ice • Display: Digital

TECHNICAL FEATURES

Free outlet maximum capacity: 570 m³/h • Motor power: 145 W • No. of filters: 1 • Anti-grease filters: Stainless steel • Filter replacement indicator: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A+ • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): NA • Annual Efficiency Consumption (AEChood): 37 kWh/a • Fluid Dynamic Efficiency (FDE): 32 • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Qmin): 370 m³/h • Air flow at maximum speed (Qmax): 470 m³/h • Air flow at boost speed (Qboost): 550 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 62 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 69 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A) • Power Consumption in Off mode (Po): 0.49 W • Time increase factor (F): 0.8 • Energy Efficiency Index: 43.4 • Measured air flow rate at best efficiency point (Qbep): 295 m³/h • Measured air pressure at best efficiency point (Pbep): 490 Pa • Measured electric power input at best efficiency point (Wbep): 125 W • Sound power level at highest setting (Lwa): 72 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 145 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 370 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 60 W

SPEED 2

Extraction rate IEC 61591: 420 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 80 W

SPEED 3

Extraction rate IEC 61591: 470 m³/h • Noise level IEC 60704-2-13: 69 dB(A) • Power: 110 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 550 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 145 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 215x115x510 • Width: 115 mm • Depth (mm): 510 mm • Product Height (mm): 215 mm • Net weight (kg): 13.300 kg • Gross weight (kg): 22.600 kg

ACCESSORIES INCLUDED

Sliding door: Yes

OPTIONAL

FLMSTPKDH12: Franges, HoodsGRIDKDH12: Filter grid, HoodsCFKDH12STD: Charcoal filter, HoodsCFKDH12HP: Charcoal filter, HoodsFLTKDH: Anti-Odour filter, Hoods



