


## KEIV90E

Hood, Decorative island hood, Universale, Stainless steel, 90 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes  
• EAN code: 8017709208745

### AESTHETICS

Colour: Stainless steel • Finishing: Glass • Aesthetics: Universale • Design: T flat • Material: Glass • Type of steel: Brushed •  
Glass Type: Clear

### PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Electronic buttons

### TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Free outlet maximum capacity: 720 m<sup>3</sup>/h • Motor power: 270 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 58 kWh/a • Fluid Dynamic Efficiency (FDE): 29.7 • Lighting Efficiency (LE): 100 lux/W • Grease Filtering Efficiency (GFE): 80 % • Air flow at minimum speed (Q<sub>min</sub>): 300 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 560 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 700 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 56 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 66 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 70 dB(A) • Power Consumption in Off mode (P<sub>o</sub>): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 53 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 390 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 460 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 168 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 440 lux • Sound power level at highest setting (L<sub>wa</sub>): 66 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 274 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1500 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 300 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 175 W

### SPEED 2

Extraction rate IEC 61591: 400 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 60 dB(A) • Power: 220 W

### SPEED 3

Extraction rate IEC 61591: 560 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 255 W

### SPEED 4

### INTENSIVE SPEED

Extraction rate (IEC 61591): 700 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 270 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 922x900x700 • Width: 900 mm • Depth (mm): 700 mm • Product Height (mm): 922 mm • Net weight (kg): 28.200 kg • Gross weight (kg): 37.900 kg

## ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC161: Charcoal filter, Hoods

