

KFAB75WH

Hood, Decorative wall hood, 50's Style , White, 75 cm, A+



TYPE

Hood width: 75 cm • Product family: Hood • Extraction: Recirculation • EAN code: 8017709224899 • Hood Type: Decorative wall hood • Electronic control: Yes

AESTHETICS

Aesthetics: 50's Style • Design: Angled • Type of steel: Brushed • Colour: White • Finishing: Glossy • Material: Painted material

CONTROLS

Control setting: Electronic buttons • Led color: White

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

TECHNICAL FEATURES

Light color temperature scale (°K): 4000 °K • Anti-grease filters: Stainless steel • Light Power: 1 W • Charcoal filters included: Yes • Minimum distance from GAS hob: 650 mm • Non return valve: Yes • No. of filters: 3 • No. of lights: 2 • Free outlet maximum capacity: 820 m³/h • Motor power: 280 W • Light type: LED • Vent outlet: 150 mm • Filter replacement indicator: Yes • Minimum distance from ELECTRIC hob: 650 mm

PERFORMANCE / ENERGY LABEL

Air flow at minimum speed (Qmin): 333 m³/h • Average illumination of the light on the cooking surface (Emiddle): 150 lux • Fluid Dynamic Efficiency class (FDEC): A • Power consumption in stand-by mode (Ps): 0.49 W • Energy efficiency class (EEC): A+ • Time increase factor (F): 0.7 • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A) • Sound power level at highest setting (Lwa): 67 dB(A) • Air flow at maximum speed (Qmax): 649 m³/h • Measured air flow rate at best efficiency point (Qbep): 421 m³/h • Fluid Dynamic Efficiency (FDE): 36.6 • Annual Efficiency Consumption (AEChood): 36 kWh/a • Grease Filtering Efficiency (GFE): 61.1 % • Grease Filtering Efficiency Class (GFEC): E • Measured air pressure at best efficiency point (Pbep): 422 Pa • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A) • Nominal Power consumption of the light system (WL): 2 W • Air flow at boost speed (Qboost): 797 m³/h • Lighting Efficiency Class (LEC): A • Lighting Efficiency (LE): 68.2 lux/W • Energy Efficiency Index: 39.7 • Measured electric power input at best efficiency point (Wbep): 135 W • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 50 dB(A)

ELECTRICAL CONNECTION

Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Electrical connection rating: 282 W

SPEED 1

Power: 198 W • Noise level IEC 60704-2-13: 50 dB(A) • Extraction rate IEC 61591: 333 m³/h

SPEED 2

Power: 246 W • Noise level IEC 60704-2-13: 59 dB(A) • Extraction rate IEC 61591: 477 m³/h

SPEED 3

Power: 286 W • Extraction rate IEC 61591: 649 m³/h • Noise level IEC 60704-2-13: 67 dB(A)

INTENSIVE SPEED

Extraction rate (IEC 61591): 797 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 294 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 644x750x616 • Width: 750 mm • Depth (mm): 616 mm • Product Height (mm): 644 mm

ACCESSORIES INCLUDED

Sliding door: Yes Remote control: Yes

OPTIONAL

FLTSI: Charcoal filter, HoodsKITCMNFABWH: Chimney set, Hoods



