


KI90CE

Hood, Decorative island hood, Universale, Stainless steel, 90 cm, B



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes
• EAN code: 8017709204068

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Chimney • Material: Stainless steel • Type of steel:
Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Buttons • Led color: White

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 600 m³/h • Motor power: 200 W • No. of filters: 3 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Minimum distance from ELECTRIC hob: 650 mm • Vent outlet: 150 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 57 kWh/a • Fluid Dynamic Efficiency (FDE): 24.1 • Lighting Efficiency (LE): 93.9 lux/W • Grease Filtering Efficiency (GFE): 80.3 % • Air flow at minimum speed (Q_{min}): 239 m³/h • Air flow at maximum speed (Q_{max}): 578 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 40 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 63 dB(A) • Time increase factor (F): 1.1 • Energy Efficiency Index: 62.3 • Measured air flow rate at best efficiency point (Q_{bep}): 333 m³/h • Measured air pressure at best efficiency point (P_{bep}): 348 Pa • Measured electric power input at best efficiency point (W_{bep}): 134 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (E_{middle}): 413 lux • Sound power level at highest setting (L_{wa}): 63 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 205 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 239 m³/h • Noise level IEC 60704-2-13: 40 dB(A) • Power: 140 W

SPEED 2

Extraction rate IEC 61591: 410 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 157 W

SPEED 3

Extraction rate IEC 61591: 578 m³/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 191 W

SPEED 4

INTENSIVE SPEED

LOGISTIC INFORMATION

Dimensions of the product (mm): 961x898x698 • Width: 898 mm • Depth (mm): 698 mm • Product Height (mm): 961 mm • Net weight (kg): 26.300 kg • Gross weight (kg): 34.800 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITALLFC: Charcoal filter, HoodsFLT6: Charcoal filter, Hoods

