


KI90XE

Hood, Decorative island hood, Universale, Stainless steel, 90 cm, B



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes
• EAN code: 8017709204044

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: T flat • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led color: White

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 66 kWh/a • Fluid Dynamic Efficiency (FDE): 27.4 • Lighting Efficiency (LE): 88.6 lux/W • Grease Filtering Efficiency (GFE): 83.1 % • Air flow at minimum speed (Q_{min}): 311 m³/h • Air flow at maximum speed (Q_{max}): 533 m³/h • Air flow at boost speed (Q_{boost}): 740 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 63 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 71 dB(A) • Power consumption in stand-by mode (P_s): 0.49 W • Energy Efficiency Index: 58.8 • Measured air flow rate at best efficiency point (Q_{bep}): 390 m³/h • Measured air pressure at best efficiency point (P_{bep}): 451 Pa • Measured electric power input at best efficiency point (W_{bep}): 171 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (E_{middle}): 390 lux • Sound power level at highest setting (L_{wa}): 63 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 279 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 311 m³/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 203 W

SPEED 2

Extraction rate IEC 61591: 385 m³/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 240 W

SPEED 3

Extraction rate IEC 61591: 533 m³/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 248 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 740 m³/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 276 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 880x900x600 • Width: 900 mm • Depth (mm): 600 mm • Product Height (mm): 880 mm • Net weight (kg): 27.100 kg • Gross weight (kg): 36.400 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITALLFC: Charcoal filter, HoodsFLT6: Charcoal filter, Hoods

