

KICGR52X

Hood, Integrated hood, Universale, Stainless steel, 52 cm, A



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 52 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709262211

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Auto-Vent: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons • Led color: Red • Display: 1 a LED

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Free outlet maximum capacity: 720 m³/h • Motor power: 270 W • No. of filters: 1 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Minimum distance from ELECTRIC hob: 550 mm • Vent outlet: 150 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 54 kWh/a • Fluid Dynamic Efficiency (FDE): 29.2 • Lighting Efficiency (LE): 73 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q_{min}): 300 m³/h • Air flow at maximum speed (Q_{max}): 600 m³/h • Air flow at boost speed (Q_{boost}): 680 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 57 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 71 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 73 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 51.7 • Measured air flow rate at best efficiency point (Q_{bep}): 382 m³/h • Measured air pressure at best efficiency point (P_{bep}): 435 Pa • Measured electric power input at best efficiency point (W_{bep}): 158 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 160 lux • Sound power level at highest setting (L_{wa}): 71 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 272 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 300 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 190 W

SPEED 2

Extraction rate IEC 61591: 450 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 230 W

SPEED 3

Extraction rate IEC 61591: 600 m³/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 255 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 680 m³/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 270 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 330x520x300 • Width: 520 mm • Depth (mm): 300 mm • Product Height (mm): 330 mm • Net weight (kg): 7.500 kg • Gross weight (kg): 9.000 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC152: Charcoal filter, HoodsKITVENT150: Valve, Hoods

