

KIR37XE

Hood, Decorative island hood, Universale, Stainless steel, 37 cm, B



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 37 cm • Extraction: Extraction • Electronic control: Yes
 • EAN code: 8017709203214

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Cylindric • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Electronic buttons • Led color: White

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Dimmer mode: Yes • Free outlet maximum capacity: 800 m³/h • Motor power: 270 W • No. of filters: 1 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 550 mm • Minimum distance from ELECTRIC hob: 550 mm • Vent outlet: 150 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): B • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 69 kWh/a • Fluid Dynamic Efficiency (FDE): 24.6 • Lighting Efficiency (LE): 118 lux/W • Grease Filtering Efficiency (GFE): 85.3 % • Air flow at minimum speed (Q_{min}): 280 m³/h • Air flow at maximum speed (Q_{max}): 560 m³/h • Air flow at boost speed (Q_{boost}): 660 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 65 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 68 dB(A) • Power Consumption in Off mode (P_o): 0.49 W • Time increase factor (F): 1.1 • Energy Efficiency Index: 51.7 • Measured air flow rate at best efficiency point (Q_{bep}): 333 m³/h • Measured air pressure at best efficiency point (P_{bep}): 447 Pa • Measured electric power input at best efficiency point (W_{bep}): 168 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 260 lux • Sound power level at highest setting (L_{wa}): 65 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 272 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 280 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 165 W

SPEED 2

Extraction rate IEC 61591: 400 m³/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 215 W

SPEED 3

Extraction rate IEC 61591: 560 m³/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 250 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 660 m³/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 270 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 770x370x370 • Width: 370 mm • Depth (mm): 370 mm • Product Height (mm): 770 mm • Net weight (kg): 22.200 kg • Gross weight (kg): 29.300 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

KITFC161: Charcoal filter, HoodsKITVENT150: Valve, HoodsRCKF2: Remote control, Hoods

