

KLT120LXS

Hood, Ceiling hood, Universale, Stainless steel, 120 cm, C



TYPE

Product family: Hood • Hood Type: Ceiling hood • Hood width: 120 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709291303

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Ceiling • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Electronic buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 7.4 W • Light color temperature scale (°K): 3000 °K • Light color temperature range: 3000° - 5700° °K • Free outlet maximum capacity: 610 m³/h • Motor power: 270 W • No. of filters: 4 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): C • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC_{hood}): 109 kWh/a • Fluid Dynamic Efficiency (FDE): 25.5 • Lighting Efficiency (LE): 14.2 lux/W • Grease Filtering Efficiency (GFE): 63.5 % • Air flow at minimum speed (Q_{min}): 196 m³/h • Air flow at maximum speed (Q_{max}): 443 m³/h • Air flow at boost speed (Q_{boost}): 597 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 56 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 61 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 68 dB(A) • Power consumption in stand-by mode (P_s): 0.38 W • Time increase factor (F): 1.1 • Energy Efficiency Index: 70.3 • Measured air flow rate at best efficiency point (Q_{bep}): 349 m³/h • Measured air pressure at best efficiency point (P_{bep}): 613 Pa • Measured electric power input at best efficiency point (W_{bep}): 233 W • Nominal Power consumption of the light system (WL): 21 W • Average illumination of the light on the cooking surface (E_{middle}): 301 lux • Sound power level at highest setting (L_{wa}): 62 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 285 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 196 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 127 W

SPEED 2

Extraction rate IEC 61591: 313 m³/h • Noise level IEC 60704-2-13: 55 dB(A) • Power: 165 W

SPEED 3

Extraction rate IEC 61591: 443 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 219 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 597 m³/h • Noise level IEC 60704-2-13: 69 dB(A) • Power: 298 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 200x1200x570 • Width: 1200 mm • Depth (mm): 570 mm • Product Height (mm): 200 mm •
Net weight (kg): 28.500 kg • Gross weight (kg): 32.500 kg

ACCESSORIES INCLUDED

Remote control: Yes

OPTIONAL

RRA90: Adaptor, Hobs, HoodsKITALLFC: Charcoal filter, HoodsKITFCKLTR: Charcoal filter, Hoods

