


KS89AOE

Hood, Decorative wall hood, Coloniale, Anthracite, 90 cm, A



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • EAN code: 8017709211868

AESTHETICS

Colour: Anthracite • Aesthetics: Coloniale • Design: Chimney • Components finishing: Antique brass • Material: Painted material • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Control knobs • Control knobs: Colonial • No. of controls: 2 • Controls colour: Old Brass

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 55 kWh/a • Fluid Dynamic Efficiency (FDE): 31 • Lighting Efficiency (LE): 90.9 lux/W • Grease Filtering Efficiency (GFE): 80.1 % • Air flow at minimum speed (Q_{min}): 331 m³/h • Air flow at maximum speed (Q_{max}): 547 m³/h • Air flow at boost speed (Q_{boost}): 788 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 63 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 71 dB(A) • Time increase factor (F): 0.9 • Energy Efficiency Index: 51.9 • Measured air flow rate at best efficiency point (Q_{bep}): 406 m³/h • Measured air pressure at best efficiency point (P_{bep}): 449 Pa • Measured electric power input at best efficiency point (W_{bep}): 164 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E_{middle}): 200 lux • Sound power level at highest setting (L_{wa}): 63 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 331 m³/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 199 W

SPEED 2

Extraction rate IEC 61591: 439 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 231 W

SPEED 3

Extraction rate IEC 61591: 547 m³/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 260 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 788 m³/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 280 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 900x899x480 • Width: 899 mm • Depth (mm): 480 mm • Product Height (mm): 900 mm • Net weight (kg): 19.300 kg

OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

