

KSDD90VN-2

Hood, Fully Integrated hood, Dolce Stil Novo, Black, 90 cm, A



TYPE

Hood width: 90 cm • Product family: Hood • Extraction: Extraction • EAN code: 8017709239336 • Hood Type: Fully Integrated hood • Perimeter extraction: Yes • Electronic control: Yes

AESTHETICS

Aesthetics: Dolce Stil Novo • Design: Fully integrated • Type of steel: Brushed • Glass Type: Black • Colour: Black • Finishing: Glass • Material: Stainless Steel + Glass

CONTROLS

Control setting: Remote Control

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

TECHNICAL FEATURES

Light color temperature scale (°K): 4000 °K • Anti-grease filters: stainless steel 7 layer • Light Power: 6 W • Non return valve: Yes • Remote motor: Included • No. of filters: 2 • No. of lights: 1 • Free outlet maximum capacity: 800 m³/h • Motor power: 285 W • Light type: LED • Vent outlet: 150 mm

PERFORMANCE / ENERGY LABEL

Air flow at maximum speed (Qmax): 500 m³/h • Measured air flow rate at best efficiency point (Qbep): 349 m³/h • Fluid Dynamic Efficiency (FDE): 30.5 • Air flow at minimum speed (Qmin): 230 m³/h • Average illumination of the light on the cooking surface (Emiddle): 253 lux • Annual Efficiency Consumption (AEC_{hood}): 53 kWh/a • Grease Filtering Efficiency (GFE): 38.9 % • Grease Filtering Efficiency Class (GFEC): G • Measured air pressure at best efficiency point (Pbep): 464 Pa • Fluid Dynamic Efficiency class (FDEC): A • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 59 dB(A) • Nominal Power consumption of the light system (WL): 6 W • Energy efficiency class (EEC): A • Time increase factor (F): 1.00 • Air flow at boost speed (Q_{boost}): 730 m³/h • Lighting Efficiency Class (LEC): A • Lighting Efficiency (LE): 40.2 lux/W • Energy Efficiency Index: 53.1 • Measured electric power input at best efficiency point (W_{bep}): 147 W • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 66 dB(A) • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 42 dB(A) • Sound power level at highest setting (L_{wa}): 59 dB(A)

ELECTRICAL CONNECTION

Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Electrical connection rating: 292 W

SPEED 1

Power: 80 W • Noise level IEC 60704-2-13: 42 dB(A) • Extraction rate IEC 61591: 230 m³/h

SPEED 2

Power: 141 W • Noise level IEC 60704-2-13: 50 dB(A) • Extraction rate IEC 61591: 322 m³/h

SPEED 3

Power: 203 W • Extraction rate IEC 61591: 500 m³/h • Noise level IEC 60704-2-13: 59 dB(A)

INTENSIVE SPEED

Extraction rate (IEC 61591): 730 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 273 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 780x900x120 • Width: 900 mm • Depth (mm): 120 mm • Product Height (mm): 780 mm

ACCESSORIES INCLUDED

Sliding door: Yes Remote control: Yes

OPTIONAL

KITKDSNRA: Frame, Hoods KITKDSNX: Frame, Hoods KITKDSNBG: Frame, Hoods FLTDSNgo: Charcoal filter, Hoods





