


KSEG7XSA

Hood, Integrated hood, Universale, Stainless steel, 70 cm, C



TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 70 cm • Extraction: Extraction • EAN code: 8017709271350

AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Electronic buttons • Led color: Red

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 5 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 691 m³/h • Motor power: 275 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 500 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): C • Fluid Dynamic Efficiency class (FDEC): C • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC_{hood}): 109 kWh/a • Fluid Dynamic Efficiency (FDE): 19.4 • Lighting Efficiency (LE): 76.1 lux/W • Grease Filtering Efficiency (GFE): 76 % • Air flow at minimum speed (Q_{min}): 288 m³/h • Air flow at maximum speed (Q_{max}): 559 m³/h • Air flow at boost speed (Q_{boost}): 691 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 54 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 70 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE_{boost}): 74 dB(A) • Power consumption in stand-by mode (P_s): 0.49 W • Time increase factor (F): 1.3 • Measured air flow rate at best efficiency point (Q_{bep}): 448 m³/h • Measured air pressure at best efficiency point (P_{bep}): 334 Pa • Measured electric power input at best efficiency point (W_{bep}): 215 W • Nominal Power consumption of the light system (WL): 10 W • Average illumination of the light on the cooking surface (E_{middle}): 761 lux • Sound power level at highest setting (L_{wa}): 70 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 285 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 288 m³/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 90 W

SPEED 2

Extraction rate IEC 61591: 428 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 95 W

SPEED 3

Extraction rate IEC 61591: 559 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 127 W

SPEED 4

INTENSIVE SPEED

Extraction rate (IEC 61591): 691 m³/h • Noise level IEC 60704-2-13: 74 dB(A) • Power: 166 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 252x724x289 • Width: 724 mm • Depth (mm): 289 mm • Product Height (mm): 252 mm • Net weight (kg): 7.400 kg • Gross weight (kg): 8.030 kg

OPTIONAL

KITFC220: Charcoal filter, Hoods

