

## KSEIR62NE2

Hood, Integrated (semi) hood, Universale, Black, 60 cm, D



### TYPE

Product family: Hood • Hood Type: Integrated (semi) hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709275099

### AESTHETICS

Colour: Black • Aesthetics: Universale • Design: Fully integrated • Material: Painted material

### PROGRAMME / FUNCTIONS

No. of speeds: 3

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 4 W • Free outlet maximum capacity: 235 m<sup>3</sup>/h • Motor power: 115 W • No. of filters: 1 • Anti-grease filters: Integrated filter • Minimum distance from GAS hob: 650 mm • Minimum distance from ELECTRIC hob: 500 mm • Vent outlet: 120 mm

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): G • Lighting Efficiency Class (LEC): E • Annual Efficiency Consumption (AEChood): 71 kWh/a • Fluid Dynamic Efficiency (FDE): 8.1 • Lighting Efficiency (LE): 9 lux/W • Grease Filtering Efficiency (GFE): 40 % • Air flow at minimum speed (Qmin): 115 m<sup>3</sup>/h • Air flow at maximum speed (Qmax): 225 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 52 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 68 dB(A) • Time increase factor (F): 1.7 • Energy Efficiency Index: 91.6 • Measured air flow rate at best efficiency point (Qbep): 125 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Pbep): 244 Pa • Measured electric power input at best efficiency point (Wbep): 105 W • Nominal Power consumption of the light system (WL): 8 W • Average illumination of the light on the cooking surface (Emiddle): 70 lux • Sound power level at highest setting (Lwa): 68 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 123 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 115 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 52 dB(A) • Power: 80 W

### SPEED 2

Extraction rate IEC 61591: 160 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 95 W

### SPEED 3

Extraction rate IEC 61591: 235 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 68 dB(A) • Power: 115 W

### SPEED 4

## INTENSIVE SPEED

## LOGISTIC INFORMATION

Dimensions of the product (mm): 150x598x300 • Width: 598 mm • Depth (mm): 300 mm • Product Height (mm): 150 mm • Net weight (kg): 6.370 kg • Gross weight (kg): 6.770 kg

## OPTIONAL

KITFC31: Charcoal filter, Hoods

