

KSET9XE2

Hood, Integrated (semi) hood, Universale, Silver, 90 cm, D



TYPE

Product family: Hood • Hood Type: Integrated (semi) hood • Hood width: 90 cm • Extraction: Extraction • EAN code: 8017709279943

AESTHETICS

Colour: Silver • Aesthetics: Universale • Design: Telescopic • Material: Stainless steel • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 4 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 520 m³/h • Motor power: 230 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 650 mm • Minimum distance from ELECTRIC hob: 450 mm • Vent outlet: 120 mm

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): D • Fluid Dynamic Efficiency class (FDEC): E • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): D • Annual Efficiency Consumption (AEC_{hood}): 127 kWh/a • Fluid Dynamic Efficiency (FDE): 9.8 • Lighting Efficiency (LE): 16 lux/W • Grease Filtering Efficiency (GFE): 75.1 % • Air flow at minimum speed (Q_{min}): 270 m³/h • Air flow at maximum speed (Q_{max}): 500 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE_{min}): 53 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE_{max}): 66 dB(A) • Time increase factor (F): 1.6 • Energy Efficiency Index: 94.8 • Measured air flow rate at best efficiency point (Q_{bep}): 306 m³/h • Measured air pressure at best efficiency point (P_{bep}): 238 Pa • Measured electric power input at best efficiency point (W_{bep}): 207 W • Nominal Power consumption of the light system (WL): 8 W • Average illumination of the light on the cooking surface (E_{middle}): 130 lux • Sound power level at highest setting (L_{wa}): 66 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 238 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1500 mm

OPTIONAL ACCESSORIES

SPEED 1

Extraction rate IEC 61591: 270 m³/h • Noise level IEC 60704-2-13: 53 dB(A) • Power: 160 W

SPEED 2

Extraction rate IEC 61591: 360 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 190 W

SPEED 3

Extraction rate IEC 61591: 500 m³/h • Noise level IEC 60704-2-13: 66 dB(A) • Power: 230 W

SPEED 4

INTENSIVE SPEED

LOGISTIC INFORMATION

Dimensions of the product (mm): 420x898x270 • Width: 898 mm • Depth (mm): 270 mm • Product Height (mm): 420 mm • Net weight (kg): 13.700 kg • Gross weight (kg): 16.440 kg

ACCESSORIES INCLUDED

Tube reduction: Yes

