

## KTS75SE2

Hood, Decorative wall hood, Linea, Stainless steel, 75 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 75 cm • Extraction: Extraction • Electronic control: Yes •

EAN code: 8017709257279

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Linea • Design: Angled • Material: Stainless steel • Type of steel: Brushed •

Glass Type: Stopsol

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons • Led color: White

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 750 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 1 • Anti-grease filters: Stainless steel • Filter replacement indicator: Yes • Minimum distance from GAS hob: 427 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 427 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): E • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 50 kWh/a • Fluid Dynamic Efficiency (FDE): 30.4 • Lighting Efficiency (LE): 103.2 lux/W • Grease Filtering Efficiency (GFE): 62.6 % • Air flow at minimum speed (Q<sub>min</sub>): 278 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 549 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 714 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 56 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 65 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 72 dB(A) • Power consumption in stand-by mode (P<sub>s</sub>): 0.49 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 51.6 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 364 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 437 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 146 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 227 lux • Sound power level at highest setting (L<sub>wa</sub>): 65 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 278 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 79 W

## SPEED 2

Extraction rate IEC 61591: 303 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 128 W

## SPEED 3

Extraction rate IEC 61591: 549 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 203 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 714 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 259 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 732x756x460 • Width: 756 mm • Depth (mm): 460 mm • Product Height (mm): 732 mm

## OPTIONAL

KITFC906: Charcoal filter, Hoods

